


TVE

Product Datasheet 1.22




Aluminium End Profile

81 Matt Silver



89 Bronze



91 Bright Silver



94 Brushed Effect



Product Description

The Aluminium edging profile accommodates LVT of 3 or 5mm deep and designed to professionally finish the edge or conceal movement, suitable for Light - Medium foot traffic in Commercial (Retail, Hospitality, education etc) and Domestic buildings.

Supplied individually packed, drilled and countersunk with Screws and Dowels.

Technical Details

Genesis Aluminium Profiles are available in different anodised finishes and powder coated finishes - All natural Aluminium (Mill Finish) has an oxide film of approx 0.2 microns, when Mechanically & Chemically polished the anodising process increases this to 5 microns, up-to 20 microns for the Matt finish and 100 for Powder coated.

Aluminium AA 6063 T6 / UNS A96063 anodised to DIN 17611

Si%	0.2-0.6
Fe%	0.35
Cu%	0.1
Mn%	0.1
Mg%	0.45-0.9
Zn%	0.1
Ti%	0.1
Cr%	0.1
Al	Balance

Dimensions

Available in lengths of 2.7m and 3 and 5mm heights.

Maintenance

Genesis TVB profiles do not require any special maintenance. Oxidation films on Aluminium may be removed with a common polishing agent; however, they do reoccur.

Damaged anodised finishes may only be repaired by re-coating. Aluminium must be tested to verify its suitability if chemical stresses are anticipated.

Cementitious materials, in conjunction with moisture, become alkaline. Since aluminium is sensitive to alkaline substances, exposure to the alkali (depending on the concentration and time of exposure) may result in corrosion (aluminium hydroxide formation). Therefore, it is important to remove adhesive or grout residue from visible surfaces. In addition, ensure that the profile is solidly embedded in the setting material and that all cavities are filled to prevent the collection of alkaline water.

The anodised layer creates a finish that retains a uniform appearance during normal use. The surface, however, is susceptible to scratching and wear and may be damaged by tile adhesive, mortar, or grouting material.

Therefore, setting materials must be removed immediately. Otherwise, the description regarding aluminium applies.

Installation

1. Clean surface thoroughly ensuring removal of any contamination that may prevent the installation.
2. Measure and cut profile to desired length.
3. Position the profile and mark the points to be drilled.
4. Reposition profile and mechanically secure using supplied fixings.

+44 (0)1642 713000 info@genesis-gs.com
www.genesis-gs.com

 **Genesis**
For the Perfect Finish